


## Ultra



| COD          | TIP             | DIMENSIUNI<br>mm | CULOARE    | U.M. | AMBALARE<br>(Cutie) |
|--------------|-----------------|------------------|------------|------|---------------------|
| 08-21003-080 | ULTRA 80x80     | 80x80x45         | PORTOCALIU | BUC  | 50                  |
| 08-21004-105 | ULTRA 105x105   | 105x105x45       | PORTOCALIU | BUC  | 40                  |
| 08-21005-155 | ULTRA 155x105   | 105x155x45       | PORTOCALIU | BUC  | 30                  |
| 08-21006-125 | ULTRA 155x125   | 125x155x50       | PORTOCALIU | BUC  | 40                  |
| 08-21007-190 | ULTRA 190x145   | 145x190x50       | PORTOCALIU | BUC  | 20                  |
| 08-21008-290 | ULTRA 290x145   | 145x290x50       | PORTOCALIU | BUC  | 10                  |
| 08-13135-003 | ULTRA H 130x130 | 130x130x55       | ROȘU       | BUC  | 44                  |
| 08-16166-004 | ULTRA H 160x160 | 160x160x65       | ROȘU       | BUC  | 20                  |
| 08-20207-005 | ULTRA H 200x200 | 200x200x70       | ROȘU       | BUC  | 12                  |



### DESCRIERE GENERALĂ

- Nu se corodează. Rezistă la impact și la presiune
- Confecționate din material polimeric special

### PROPRIETĂȚI

Grad de protecție corpuri solide și apă  
Glow wire test  
Temperatura limită inferioară  
Temperatura limită superioară

IP 20  
650°C  
-15°C  
+60°C

**STANDARDE APLICATE: IEC 60670-1/2002**

