




# HALOGEN



GU4



GU5.3



GU10



CLASA  
ENERGETICĂ



GU4 /  
GU5.3



2.000 H



2800



DICROIC 35/  
DICROIC 50



DIMABIL

Surse de iluminat - HALOGENE

| COD               | MODEL        | P <sub>(i)</sub> | Flux   | Unghi de<br>dispersie | Tens. de<br>alimentare | Soclu | Formă | Dimensiuni<br>(LxA) | Stocabil |
|-------------------|--------------|------------------|--------|-----------------------|------------------------|-------|-------|---------------------|----------|
| unitate de masură |              | W                | lm     | °                     | V                      |       |       | mm                  |          |
| EL0009517         | TG-2202.0120 | 20               | 180    | 20°                   | 12                     | GU4   |       | 35x35               | ✓        |
| EL0009518         | TG-2202.0135 | 35               | 350    | 20°                   | 12                     | GU4   |       | 35x35               | ✓        |
| EL0009519         | TG-2202.0150 | 50               | 400    | 20°                   | 12                     | GU4   |       | 35x35               | ✓        |
| EL0025160         | TG-2202.0220 | 20               | 120    | 30°                   | 230                    | GU4   |       | 45x35               | ✓        |
| EL0025161         | TG-2202.0235 | 35               | 270    | 30°                   | 230                    | GU4   |       | 45x35               | ✓        |
| EL0025162         | TG-2202.0250 | 50               | 400    | 30°                   | 230                    | GU4   |       | 45x35               | ✓        |
| EL0009514         | TG-2203.0120 | 20               | 180    | 24°                   | 12                     | GU5.3 |       | 45x50               | ✓        |
| EL0009515         | TG-2203.0135 | 35               | 350    | 24°                   | 12                     | GU5.3 |       | 45x50               | ✓        |
| EL0009516         | TG-2203.0150 | 50               | 600    | 24°                   | 12                     | GU5.3 |       | 45x50               | ✓        |
| EL0009511         | TG-2204.0120 | 20               | 120    | 40°                   | 230                    | GU5.3 |       | 45x50               | ✓        |
| EL0009512         | TG-2204.0135 | 35               | 270    | 40°                   | 230                    | GU5.3 |       | 45x50               | ✓        |
| EL0009513         | TG-2204.0150 | 50               | 400    | 40°                   | 230                    | GU5.3 |       | 45x50               | ✓        |
| EL0011018         | TG-2204.1150 | 50               | Bleu   | 40°                   | 230                    | GU5.3 |       | 45x50               | ✓        |
| EL0011021         | TG-2204.3150 | 50               | Verde  | 40°                   | 230                    | GU5.3 |       | 45x50               | ✓        |
| EL0011019         | TG-2204.4150 | 50               | Galben | 40°                   | 230                    | GU5.3 |       | 45x50               | ✓        |
| EL0004664         | TG-2205.0135 | 35               | 195    | 40°                   | 230                    | GU10  |       | 55x50               | ✓        |
| EL0004665         | TG-2205.0150 | 50               | 300    | 40°                   | 230                    | GU10  |       | 55x50               | ✓        |
| EL0004666         | TG-2205.0175 | 75               | 675    | 40°                   | 230                    | GU10  |       | 55x50               | ✓        |



DIMENSIUNI  
BAX



BUC./BAX



KG / BAX