

Article**517.3257**

SOCKET OUTLET 3P+N+E IP67 32A 6h

Picture**Master data**

Minimum order	10 NR
Net Weight	0.373 KG
EAN code	8001636072548
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	OPTIMA Series
Synthetical description	SURFACE MOUNTING SOCKET
Rated current	32A
Poles	3P+N+E
Hour position	6h
Rated voltage (range)	250-400V
Rated voltage	346-415V
Working frequency	50Hz
Working frequency	60Hz
Colour	RED
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Types of available outlets	ANGLED
Terminals	Screw terminals
Cable outlet	M32X1,5

Approvals and Certifications
 UE
 Declaration of conformity

 I.M.Q. - ENEC 03
 European Norms Electrical Certification
Standards and Laws
 EN 60309-1 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EAC
Eurasian Conformity



CQC (China)
China Quality Certification mark



EN 60309-2 (1999)
[European Standard] Plugs, socket-outlets
and couplers for industrial purposes. Part 2:
Dimensional interchangeability requirements
for pin and contact-tube accessories of
harmonized configurations

Packaging

Description	Carton
Quantity	40
EAN code	8001636887715
Gross weight	16.4 KG
Volume	77123.75 CCM
Dimensions	355x550x395 (MM)
Description	Box
Quantity	10
EAN code	8001636887722
Gross weight	4.1 KG
Volume	14857.92 CCM
Dimensions	268x308x180 (MM)

Annexed



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]

Note:



Open threaded cable entry



Threaded cap/cable sleeve included

