

Article**218.12530**

PLUG 2P+E IP66/IP67 125A 4h 100-130V AC

Picture**Master data**

Minimum order	1 NR
Net Weight	1.093 KG
EAN code	8001636224602
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	OPTIMA Series
Synthetical description	PLUG
Rated current	125A
Poles	2P+E
Hour position	4h
Rated voltage (range)	50-200V
Rated voltage	100-130V
Working frequency	50Hz
Working frequency	60Hz
Colour	YELLOW
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Types of available outlets	STRAIGHT
Terminals	Mantle terminals
Cable outlet	CABLE GLAND

Approvals and Certifications
 UE
 Declaration of conformity

 I.M.Q. - ENEC 03
 European Norms Electrical Certification

 EN 60309-1 (1999)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 1:
 General requirements
Standards and Laws



EAC
Eurasian Conformity



CQC (China)
China Quality Certification mark



EN 60309-2 (1999)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A1 (2007)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A1 (2007)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A2 (2012)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A2 (2012)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations

Packaging

Description	Carton
Quantity	8
EAN code	8001636675879
Gross weight	11.616 KG
Volume	87100 CCM
Dimensions	400x650x335 (MM)
Description	Box
Quantity	1
EAN code	
Gross weight	1.452 KG
Volume	7497 CCM
Dimensions	140x315x170 (MM)

Annexed



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]

Articoli Collegati:

	570.9125	PLUG CAP 100A 125A GREY
--	----------	-------------------------