

Article

413.1667
 FLUSH-MOUNTING SOCKET 3P+N+E IP44 16A 6h

Picture**Master data**

Minimum order	10 NR
Net Weight	0.155 KG
EAN code	8001636244839
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	OPTIMA Series
Synthetical description	FLUSH-MOUNTING SOCKET
Rated current	16A
Poles	3P+N+E
Hour position	6h
Rated voltage (range)	250-400V
Rated voltage	346-415V
Working frequency	50Hz
Working frequency	60Hz
Colour	RED
Protection degree	Splash proof
Protection degree IP	IP44/IP54
Types of available outlets	ANGLED
Terminals	Screw terminals
Flange	70X87MM

Approvals and Certifications

UE
 Declaration of conformity



I.M.Q. - ENEC 03
 European Norms Electrical Certification

Standards and Laws

EN 60309-1 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EAC
Eurasian Conformity



CQC (China)
China Quality Certification mark



EN 60309-2 (1999)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A1 (2007)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A1 (2007)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A2 (2012)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A2 (2012)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations

Packaging

Description	Carton
Quantity	100
EAN code	8001636692784
Gross weight	17.7 KG
Volume	84072 CCM
Dimensions	240x565x620 (MM)
Description	Box
Quantity	10
EAN code	8001636692777
Gross weight	1.77 KG
Volume	7128 CCM
Dimensions	220x270x120 (MM)

Annexed



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]

Articoli Collegati:

	570.0016	SURFACE MOUNTING BOX 16A IP67 STRAIGHT
	570.0116	SURFACE MOUNTING BOX 16A IP67 ANGLED

	570.M0016	SURFACE MOUN.STRAIGHT BOX FOR 16A OUTLET
	570.M0116	SURFACE MOUN. ANGLED BOX FOR 16A OUTLET