

Article**517.1657**

SOCKET OUTLET 3P+N+E IP67 16A 6h

Picture**Master data**

Minimum order	10 NR
Net Weight	0.255 KG
EAN code	8001636072265
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	OPTIMA Series
Synthetical description	SURFACE MOUNTING SOCKET
Rated current	16A
Poles	3P+N+E
Hour position	6h
Rated voltage (range)	250-400V
Rated voltage	346-415V
Working frequency	50Hz
Working frequency	60Hz
Colour	RED
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Types of available outlets	ANGLED
Terminals	Screw terminals
Cable outlet	M25X1,5

Approvals and Certifications
 UE
 Declaration of conformity

 I.M.Q. - ENEC 03
 European Norms Electrical Certification

 EN 60309-1 (1999)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 1:
 General requirements
Standards and Laws



EAC
Eurasian Conformity



CQC (China)
China Quality Certification mark



EN 60309-2 (1999)
[European Standard] Plugs, socket-outlets
and couplers for industrial purposes. Part 2:
Dimensional interchangeability requirements
for pin and contact-tube accessories of
harmonized configurations

Packaging

Description	Carton
Quantity	40
EAN code	8001636888279
Gross weight	11.04 KG
Volume	77123.75 CCM
Dimensions	355x550x395 (MM)
Description	Box
Quantity	10
EAN code	8001636888286
Gross weight	2.76 KG
Volume	15318.435 CCM
Dimensions	263x353x165 (MM)

Annexed



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]



Note:

> Open threaded cable entry 

> Threaded cap/cable sleeve included 