

Article**518.12557T**

SURF.MNT.SOCKET 3P+N+E IP66/IP67 125A 6h

Picture**Master data**

Minimum order	1 NR
Net Weight	1.777 KG
EAN code	8001636311548
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	OPTIMA-TOP Series
Synthetical description	SURFACE MOUNTING SOCKET
Rated current	125A
Poles	3P+N+E
Hour position	6h
Rated voltage (range)	250-400V
Rated voltage	346-415V
Working frequency	50Hz
Working frequency	60Hz
Colour	RED
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Types of available outlets	ANGLED
Terminals	Mantle terminals
Cable outlet	M63X1,5

Approvals and Certifications

I.M.Q. - ENEC 03
 European Norms Electrical Certification



EAC
 Eurasian Conformity

**Standards and Laws**

EN 60309-2/A1 (2007)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



CQC (China)
China Quality Certification mark



UE
Declaration of conformity



EN 60309-1/A1 (2007)
[European Standard] Plugs, socket-outlets
and couplers for industrial purposes. Part 1:
General requirements



EN 60309-2 (1999)
[European Standard] Plugs, socket-outlets
and couplers for industrial purposes. Part 2:
Dimensional interchangeability requirements
for pin and contact-tube accessories of
harmonized configurations



EN 60309-1 (1999)
[European Standard] Plugs, socket-outlets
and couplers for industrial purposes. Part 1:
General requirements



EN 60309-1/A2 (2012)
[European Standard] Plugs, socket-outlets
and couplers for industrial purposes. Part 1:
General requirements



EN 60309-2/A2 (2012)
[European Standard] Plugs, socket-outlets
and couplers for industrial purposes. Part 2:
Dimensional interchangeability requirements
for pin and contact-tube accessories of
harmonized configurations

Packaging

Description	Carton
Quantity	4
EAN code	8001636752730
Gross weight	8.628 KG
Volume	72450 CCM
Dimensions	375x560x345 (MM)
Description	Box
Quantity	1
EAN code	
Gross weight	2.157 KG
Volume	14857.92 CCM
Dimensions	268x308x180 (MM)

Annexed



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]

Note:

- > Open threaded cable entry ☐
- > Cable gland included ☐
- > Threaded cap/cable sleeve included ☐