

DESCRIPTION

Premium acrylic paint with excellent gloss, adhesion, and resistance to weather conditions. Contains acrylic, hydrocarbon and special resins, organic and inorganic pigments, aromatic, aliphatic hydrocarbons as solvents.

FEATURES

- Extraordinary gloss.
- Unique design for each color.
- Fast drying.
- Excellent elasticity.
- Easy to apply and recoat.
- Exceptional adhesion.
- Very good resistance to the sun and rain.
- Rust preventative.
- Fade and chip resistant.

INSTRUCTIONS FOR USE

Shake the container at least 3 minutes after you hear the ball mixer. Before the first use spray it in the air for 3-4 seconds to remove any condensed color. Spray at a distance of 30cm from the surface. Try the spray on testing surface. For better results apply 2-3 thin coats, 3-5 min apart. It allows a later varnishing. If the nozzle is blocked, replace it with a new one. Use outdoors or in a well-ventilated area such as an open garage. Use when temperature is between 10-32°C and humidity is below 65% to ensure proper drying. Do not use on objects that may exceed 90°C surface temperature. After use spray while holding the can inverted for 3 seconds. Clean the actuator with solvent. Storage 10-30°C. Do not put in vehicles. Ask for MSDS

SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or sandpaper. Previously coated surfaces must be sound and in good condition. Smooth, hard, or glossy finishes should be scarified by sanding to create a surface profile. In plastics like PS and PP apply first a primer layer.

PHYSICAL PROPERTIES

Propellant: butane/propane mixture
 Viscosity: 18-25 sec (Flow Cup DIN4, 20°C)
 Density: 0.70 – 0.75 kg/L (Density Cup 100cm³/20°C, ASTM D – 1475)
 Solids: 13-18 % Flash Point -104 °C (based on propellant)
 Drying time: Touch (20°C, Humidity<65%): 5-10min Through dry (20°C, Humidity <65%) : 1h
 Maximum hardness: 24 hours
 Coverage: 3m² per 400ml or 3,75m² per 500ml
 Gloss: 80-95 GLOSS [GLOSS METER 600ASTM D – 1471], 30-50 SEMI GLOSS, 0-10 FLAT
 Film thickness: 200µm (wet), 40-45µm (dry) Can Pressure 4bar (20°C) , 8 bar (50°C)
 Contents: 400ml/315grams (net)
 Shelf life: minimum 5 years.
 VOC CONTENT: 650 g/L

APPLICATIONS

Ideal for DIY or professional use on most surfaces: wood, metal, stainless steel, glass, plaster, ceramics, stone, fabric, paper and others.

APPEARANCE

BOTTLE
 Indicates the paint color




CAP SYSTEM



Standard Cap
 Thin and regular

CAUTION



PINDOU 1 & SIGGROU 242 AVENUE, 176 72 ATHENS / GREECE
 T +30210 957 0222 F +30210 956 6671 E support@cosmoslac.com

ISO 9001:2000
 Made in Europe